

# OPT++

## An Object-Oriented Toolkit for Nonlinear Optimization

**Ricardo Oliva**

**Juan Meza**

High Performance Computing Research  
Lawrence Berkeley National Laboratory

<http://crd.lbl.gov/~meza>

# Outline

---

- ❖ Introduction to Optimization
- ❖ OPT++ Philosophy
- ❖ OPT++ Problem and Solver Classes
- ❖ Quick Tour of Algorithms
- ❖ Parallel optimization techniques
- ❖ Setting up a Problem and Algorithm
  - Example 1: Unconstrained Optimization
  - Example 2: Constrained Optimization
  - Example 3: Protein Folding
- ❖ Summary

# Introduction

---

- ❖ OPT++ is an open source toolkit for general nonlinear optimization problems
- ❖ Original development started in 1992 at Sandia National Labs/CA
- ❖ Major contributors
  - Juan Meza, LBNL
  - Ricardo Oliva, LBNL
  - Patty Hough, SNL/CA
  - Pam Williams, SNL/CA

# Global OPTimization

---




Total = 338


Other (Country not identified) = 120

As of April, 2003

# Simulation-based optimization problems




- ❖ Predict properties of nanostructures or design nanostructures with desired properties



- ❖ Protein folding problem: *Predicting the natural configuration of a protein from its amino sequence.* Optimization approach: Find the configuration that minimizes an energy potential model (AMBER)

# Parameter identification example

---




- ❖ Find model parameters, satisfying some bounds, for which the simulation matches the observed temperature profiles
- ❖ Computing objective function requires running thermal analysis code
- ❖ Each simulation requires approximately 7 hours on 1 processor



# Formulation of parameter ID problem

$$\begin{array}{ll} \min_x & \sum_{i=1}^N (T_i(x) - T_i^*)^2 \\ \text{s. t.} & 0 \leq x \leq u \end{array}$$

Maximum Temperature Difference



- ❖ Objective function consists of computing the temperature difference between simulation results and experimental data
- ❖ Optimization landscape contains many local minima
- ❖ Uncertainty in both the measurements and the model parameters

# General Optimization Problem

---

$$\min_{x \in \mathcal{R}^n} f(x),$$

Objective function

$$s.t. \quad h(x) = 0,$$

Equality constraints

$$g(x) \geq 0$$

Inequality constraints

$$L = f(x) + y^T h(x) - w^T g(x)$$



# Optimization Problem Types

---

- ❖ Unconstrained optimization
- ❖ Bound constrained optimization
  - Only upper and lower bounds
  - Sometimes called “box” constraints
- ❖ General nonlinearly constrained optimization
  - Equality and inequality constraints
  - Usually nonlinear
- ❖ Some special case classes (not currently handled in OPT++)
  - Linear programming (function and constraints linear)
  - Quadratic programming (quadratic function, linear constraints)

# Some working assumptions

---

- ❖ Objective function is smooth
  - Usually true, but simulations can create noisy behavior
- ❖ Twice continuously differentiable
  - Usually true, but difficult to prove
- ❖ Constraints are linearly independent
  - Users can sometimes over-specify or incorrectly guess constraints
- ❖ Inexpensive objective functions

# OPT++ Philosophy

---

- ❖ Problem should be defined in terms the user understands
  - *Do I have second derivatives available?* and not *Is my objective function twice continuously differentiable?*
  - *Is my function expensive to compute ?*
- ❖ Solution methods should be easily interchangeable
  - Once the problem is set up, methods should be easy to interchange so that the user can compare algorithms
- ❖ Common components of algorithms should be interchangeable
  - Algorithm developers should be able to re-use common components from other algorithms, for example line searches, step computations, etc.

# Classes of Problems in OPT++

---

## ❖ Four major classes of problems available

- *NLF0*(*ndim*, *fcn*, *init\_fcn*, *constraint*)
  - Basic nonlinear function, no derivative information available
- *NLF1*(*ndim*, *fcn*, *init\_fcn*, *constraint*)
  - Nonlinear function, first derivative information available
- *FDNLF1*(*ndim*, *fcn*, *init\_fcn*, *constraint*)
  - Nonlinear function, first derivative information approximated
- *NLF2*(*ndim*, *fcn*, *init\_fcn*, *constraint*)
  - Nonlinear function, first and second derivative information available

# Classes of Solvers in OPT++

---

- ❖ Direct search
  - No derivative information required
- ❖ Conjugate Gradient
  - Derivative information may be available but doesn't use quadratic information
- ❖ Newton-type methods
  - Algorithm attempts to use/approximate quadratic information
  - Newton
  - Finite-Difference Newton
  - Quasi-Newton
  - NIPS

# Constraints

---

## ❖ Constraint types

- BoundConstraint
- LinearInequality
- NonLinearInequality
- LinearEquation
- NonLinearEquation

## ❖ Everything combined


- CompoundConstraint

# Quick tour of some of the algorithms



# Pattern search

---



- ❖ Can handle noisy functions
- ❖ Do not require derivative information
- ❖ Inherently parallel
- ❖ Convergence can be painfully slow

# Conjugate Gradient Methods

---


## ❖ Standard nonlinear conjugate gradient

- Two different types of line searches
  - mcsrch (Moré & Thuente)
  - Backtrack with cubic fit.

## ❖ Limited Memory BFGS

- Unconstrained version available
- Bound-constrained under development.
- Suitable for large-scale problems

# Newton-type Methods



- ❖ Fast convergence properties
- ❖ Good global convergence properties
- ❖ Inherently serial
- ❖ Difficulties with noisy functions

# NIPS: Nonlinear Interior Point Solver

---

- ❖ Interior point method
- ❖ Based on Newton's method for a particular system of equations (perturbed Karush-Kuhn-Tucker, KKT, equations, slack variable form)
- ❖ Can handle general nonlinear constraints
- ❖ Can handle strict feasibility in most cases

$$F(\mu) = \begin{bmatrix} \nabla f(x) + \nabla h(x)y - \nabla g(x)w \\ w - z \\ h(x) \\ g(x) - s \\ ZSe - \mu e \end{bmatrix} = 0$$


# Parallel Optimization

# Schnabel Identified Three Levels for Introducing Parallelism Into Optimization (1995)

---

- ❖ Parallelize evaluation of function/gradient/constraints
  - May or may not be easy to implement
- ❖ Parallelize linear algebra
  - Really only useful if the optimization problem is large-scale
- ❖ Parallelize optimization algorithm at a high level, for example, multiple function evaluations in parallel
  - Parallel Direct Search
  - Generalized Pattern Search
  - TRPDS
  - TRGSS

# Trust Region + PDS



- ❖ Fast convergence properties of Newton method
- ❖ Good global convergence properties of trust region approach
- ❖ Inherent parallelism of PDS
- ❖ Ability to handle noisy functions



# Algorithm Choices Depend on Problem

	NLF0	FDNLF1	NLF1	NLF2
OptPDS	X	X	X	X
OptGSS	X	X	X	X
OptCG		X	X	X
OptLBFGS		X	X	X
OptQNewton		X	X	X
OptBCQNewton		X	X	X
OptFDNewton		X	X	X
OptFDNIPS		X	X	X
OptNewton				X
OptBCNewton				X
OptNIPS				X

# Example 1: unconstrained optimization

---

```
void init_rosen_x0(int ndim, ColumnVector& x);  
void rosen(int ndim, const ColumnVector& x, double& fx, int& result);  
  
int main() {  
    int ndim = 2;  
    FDNLF1 nlp(ndim, rosen, init_rosen_x0);  
    nlp.initFcn();  
    OptQNewton objfcn(&nlp);  
    objfcn.setSearchStrategy(TrustRegion);  
    objfcn.setMaxFeval(200);  
    objfcn.setFcnTol(1.e-4);  
    objfcn.optimize();  
}
```

# Example 2: Constrained optimization

---

## Hock-Schittkowski Test Problem #65

$$\min (x_1 - x_2)^2 + (1/9)(x_1 + x_2 - 10)^2 + (x_3 - 5)^2$$

*s.t.*

$$x_1^2 + x_2^2 + x_3^2 \leq 48,$$

$$-4.5 \leq x_1 \leq 4.5,$$

$$-4.5 \leq x_2 \leq 4.5,$$

$$-5.0 \leq x_3 \leq 5.0$$

# Constrained optimization: Step 1

---

Defining the bound constraints:

$$-4.5 \leq x_1 \leq 4.5,$$

$$-4.5 \leq x_2 \leq 4.5,$$

$$-5.0 \leq x_3 \leq 5.0$$

```
int ndim = 3;
```

```
ColumnVector lower(ndim), upper(ndim);
```

```
lower << -4.5 << -4.5 << -5.0;
```

```
upper << 4.5 << 4.5 << 5.0 ;
```

```
Constraint bc = new BoundConstraint(ndim, lower, upper);
```

# Constrained optimization: Step 2

---

Defining the nonlinear inequality constraint:

$$x_1^2 + x_2^2 + x_3^2 \leq 48$$

```
NLP* chs65 = new NLP(new NLF2(ndim, 1, ineq, init_hs65_x0));
```

```
Constraint nleqn = new NonLinearInequality(chs65);
```

Collecting both constraints into one constraint object :

```
CompoundConstraint* constraints =  
    new CompoundConstraint(nleqn, bc);
```

# Constrained optimization: Step 3

---

Defining and initializing the nonlinear problem:

```
NLF2 nips(ndim, hs65_2, init_hs65_x0, constraints);  
nips.initFcn();
```

Defining the Optimization object and optimizing it!

```
OptNIPS optobj(&nips);  
optobj.optimize();
```


# Application: Protein Folding

---

```
void init_X0(int ndim, ColumnVector& x);  
void eval_energy(int ndim, const ColumnVector& x, double& fx, int&  
    result);  
int main() {  
    PDB pdb("t162.pdb"); // loads pdb file  
    int ndim = 3 * pdb.NumAtoms();  
    FDNLF1 nlp(ndim, eval_energy, init_X0);  
    nlp.initFcn();  
    OptLBFGS optobj(&nlp);  
    optobj.setMaxFeval(10000);  
    optobj.setFcnTol(1.e-6);  
    optobj.optimize();  
}
```




# Energy Minimization Using LBFGS



Created by R. Oliva and C. Siegerist, LBNL

- ❖ Energy Function: AMBER
- ❖ Protein **T209** (CASP6)
- ❖  $N = 6729$  (2243 Atoms)
- ❖ LBFGS with  $M=15$
- ❖ Total number of LBFGS iterations = 71178
- ❖ Total number of function evaluations = 72758
- ❖ Each function evaluation takes approximately 2 CPU sec

# Protein T209 (from CASP6)



- ❖ Initial configuration created using ProteinShop (S.Crivelli)
- ❖ Energy minimization computed using OPT++/LBFGS
- ❖ Total simulation took approximately 62 hours on a 2.0 GHz Macintosh G4 with 2Gb RAM

Created by R. Oliva and C. Siegerist, LBNL

# Summary

---

- ❖ OPT++ can handle many types of nonlinear optimization problems
- ❖ The toolkit can be used to compare the effectiveness of several algorithms on the same problem easily
- ❖ The user needs to provide only functions for the objective function and the constraints
  - If additional information is available it can be easily incorporated
- ❖ The code is open source and available at either
  - <http://www.nersc.gov/~meza/projects/opt++>
  - <http://csmr.ca.sandia.gov/opt++>

# Backup Material

# References

---


## ❖ Other links

- <http://sal.kachinatech.com/B/3/index.shtml>
- <http://www-neos.mcs.anl.gov/neos>
- <http://www.mcs.anl.gov/tao>
- <http://endo.sandia.gov/DAKOTA/index.html>

## ❖ Books/Papers

- Dennis and Schnabel, *Numerical Methods for Unconstrained Optimization and Nonlinear Equations*, Prentice-Hall, 1983
- Gill, Murray, Wright, *Practical Optimization*, Academic Press, 1981
- El-Bakry, Tapia, Tsuchiya, Zhang, *On the Formulation and Theory of the Newton Interior-Point Method for Nonlinear Programming*, JOTA, Vol. 89, No.3, pp.507-541, 1996
- More' and Wright, *Optimization Software Guide*, SIAM, 1993


# Comparison of TRPDS with other approaches



## PDE Relative Convergence Tolerance


Fifth Workshop on the DOE Advanced Computational Software Collection  
Berkeley, CA, August 24-27, 2004

# Energy vs. LBFGS iterations for T162 Problem





# T162 Protein: $\| \text{gradient} \|$ by atom



# Distribution of $\| \text{gradient} \|$ by atom

